Product Specification/Data Sheet

era
bespoke - flexible - service

PRODUCT DETAILS:

Product Name:	Gemini
Product Type:	Screen: floor standing
Product Shape:	Straight
Product Code:	G(D/T/Q)/XX.XXFS

PRODUCT IMAGE:



SPECIFICATION:

- Consists of a 27mm thick fabric screen.
- Screen height available between 1200mm and 1600mm.
- Screen width available between 800mm and 1200mm.
- Internal panel construction is from 25mm double laminate pinnable kraft lined board with strengthening battens constructed from 18mm MDF mechanically pinned to panel edges, with 50mm radius corners.
- Internal panel is upholstered (with a double top stitch) in 1mm thick Camira fabric, generally from the Cara, Blazer Lite, Synergy or Blazer ranges.
- Each panel is supplied with either 1 or 2 x white or black 10mm open end zip heavy duty no.10 moulded teeth with double metal sliders which act as inline linking strips.
- Screens are supplied with 2 x height adjusting feet which provide 35mm of adjustment to allow for uneven floors.
- 18mm MDF is Programme for the Endorsement of Forest Certification (PEFC) 1 min 100% and Forest Stewardship Council (FSC) certified.
- On average each screen is manufactured from materials with 38% recycled content.
- On average each screen is manufactured from materials with 82% recyclable content.
- Screens are packaged with a single polythene bag.

SUPPLIED WITH:

- Each panel is supplied with either 1 or 2 x white or black 10mm open end zip heavy duty no.10 moulded teeth with double metal sliders which act as inline linking strips.
- Screens are supplied with 2 x height adjusting feet which provide 35mm of adjustment to allow for uneven floors.

CERTIFICATIONS:

- Typical Camira fabrics used are Cara, Blazer Lite, Synergy or Blazer which have flammability performance as follows, Cara: EN 1021-1 (cigarette), BS 476 Part 7 Class 1 (Adhered), EN 13501-1 Adhered Class B, s2, d0. Blazer Lite: BS 476 Part 7 Class 1 (Adhered), BS 476 Part 6 Class 0 (Adhered), EN 13501-1 Adhered Class C, s1, d0. Synergy: EN 1021 - 1 (cigarette), EN 1021 - 2 (match), BS 7176 Low Hazard, NF D 60-013, ÖNORM B 3825 & A 3800-1, (58 kg/m3 CMHR Foam), UNI 9175 Classe 1 IM, EN 13501-1 Adhered Class D, s1, d0, EN 13501-1 Un-adhered Class E, s2, d0. Blazer: same as Synergy plus BS 476 Part 7 Class 1 (Adhered).
- Conforms to BSEN 1023 part 1.
- Tested by the Furniture Industry Research Association (FIRA) and certified to BSEN 1023 parts 2 & 3 - report reference TRELF32922.

Unit 1 Era Park
Upper Clatford
Hampshire
SP11 7LW

First Floor
10 Great Sutton Street
London
EC1V 0BX

t: +44 (0) 1264 341400
f: +44 (0) 1264 341444
e: sales@erascreens.com
w: www. erascreens.com

Company reg no: 04195401
Vat no: 780 7693 87