

# Product Specification/Data Sheet

## PRODUCT DETAILS:

Product Name:	Minoro
Product Type:	Screen: desk mounted or floor standing
Product Shape:	Straight
Product Code:	MIN/XX.XXD/FS

## PRODUCT IMAGE:



## SPECIFICATION:

Consists of a 49mm thick fabric screen for desk mounted and 52mm thick for floor standing both with 4 x 67mm radius corners.

Screen height available between 250mm and 1800mm.

Screen width available between 400mm and 1600mm.

Internal panel construction for desk mounted is from 9mm medium density fibreboard (MDF) centre surrounded by 18mm MDF 50mm wide frame on both sides.

Internal panel construction for floor standing is from 12mm medium density fibreboard (MDF) centre surrounded by 18mm MDF 50mm wide frame on both sides.

Each panel face is finished with 18mm thick sound absorbing foam and Dacron polyester wadding.

Sound absorbing foam is tested to BSEN ISO 354 and has a noise reduction co-efficient (NRC) of 0.43 (inferred) resulting in overall NRC of 0.86 per panel. Technical report ref no: C/23213/T01.

Internal panel is upholstered (with a double top stitch) in 1mm thick Camira fabric, generally from the Cara, Blazer Lite, Synergy or Blazer ranges.

Thread is supplied in closest colour match to available stock.

Desk mounted screens are supplied with 2 x spigot brackets to suit 25mm desk tops (code: FJ25) which are fitted to the bottom of the panel.

Desk mounted screens are manufactured 5mm lower than the ordered height to allow for the standard bracket thickness.

Standard bracket hole positions are 200mm in from each screen edge unless screen width is smaller than 800 wide then these will be 75mm - others available on request.

FJ25 brackets are pressure die cast from aluminium and powder coated.

Floor standing screens are supplied with 2 x height adjusting feet which provide 35mm of adjustment to allow for uneven floors.

Floor standing screens are supplied with 2 x stabilising feet manufactured from mild steel and powder coated.

Standard bracket and feet colours are Polybond Regal silver metallic gloss epoxy polyester and RAL 9016 white gloss polyester.

9mm, 12mm and 18mm MDF is Forest Stewardship Council® (FSC®) certified (FSC-C200033).

On average each screen is manufactured from materials with 38% recycled content.

On average each screen is manufactured from materials with 82% recyclable content.

Screens are packaged with a single polythene bag.

## SUPPLIED WITH:

Desk mounted screens are supplied with 2 x spigot brackets to suit 25mm desk tops (code: FJ25) which are fitted to the bottom of the panel.

Floor standing screens are supplied with 2 x height adjusting feet which provide 35mm of adjustment to allow for uneven floors.

Floor standing screens are supplied with 2 x stabilising feet manufactured from mild steel and powder coated.

## CERTIFICATIONS:

Typical Camira fabrics used are Cara, Blazer Lite, Synergy or Blazer which have flammability performance as follows, Cara: EN 1021-1 (cigarette), BS 476 Part 7 Class 1 (Adhered), EN 13501-1 Adhered Class B, s2, d0. Blazer Lite: BS 476 Part 7 Class 1 (Adhered), BS 476 Part 6 Class 0 (Adhered), EN 13501-1 Adhered Class C, s1, d0. Synergy: EN 1021 - 1 (cigarette), EN 1021 - 2 (match), BS 7176 Low Hazard, NF D 60-013, ÖNORM B 3825 & A 3800-1, (58 kg/m3 CMHR Foam), UNI 9175 Classe 1 IM, EN 13501-1 Adhered Class D, s1, d0, EN 13501-1 Un-adhered Class E, s2, d0. Blazer: same as Synergy plus BS 476 Part 7 Class 1 (Adhered).

Conforms to BSEN 1023 part 1.

Tested by the Furniture Industry Research Association (FIRA) and certified to BSEN 1023 parts 2 & 3 - report reference TREL32922.

Unit 1 Era Park  
Upper Clatford  
Hampshire  
SP11 7LW

First Floor  
10 Great Sutton Street  
London  
EC1V 0BX

t: +44 (0) 1264 341400  
f: +44 (0) 1264 341444  
e: [sales@erascreens.com](mailto:sales@erascreens.com)  
w: [www.erascreens.com](http://www.erascreens.com)

Company reg no: 04195401  
Vat no: 780 7693 87

