


Product Specification/Data Sheet

PRODUCT DETAILS:		PRODUCT IMAGE:
Product Name:	FLO	
Product Type:	Screen: Mobile or Floor Standing	
Product Shape:	Straight	
Product Code:	FLO/XX.XX.XX	

SPECIFICATION:
Made from 60% recycled PET (Polyethylene terephthalate)(from used plastic bottles).
PET core is 100% recyclable at end of life.
Available in 12mm in 26 colours.
12mm PET is tested to BSEN ISO 354 and has a noise reduction co-efficient (NRC) of 0.45 (Class E).
Not affected by moisture, mould or mildew.
No formaldehyde binders.
Low VOCs.
Bespoke panels can be created from your designs.
Screen height available between 400mm and 2000mm.
Screen width available between 600mm and 2000mm.
Each screen is supplied with 2 x stabilising mobile feet manufactured from mild steel and powder coated to match frame.
Each mobile foot is supplied with 2 x castor feet (75mm diameter) manufactured from thermoplastic with rubber trim finished in metallic silver with grey trim (1 x castor is locking).
A range of accessories are available, including tool rails, shelving, name plates, paper trays and monitor arms.
On average each screen is manufactured from materials with 60% recycled content.
On average each screen is manufactured from materials with 85% recyclable content.
Screens are packaged with a single polythene bag.
Consists of a 33mm thick full aluminium framed screen.
Aluminium frame is 16mm high x 23mm wide (visible) extruded from 6063 T6 Tensile strength aluminium.
Aluminium frame is epoxy powder coated in Reichsausschuß für Lieferbedingungen (RAL) or British Standard BS4800:2011 Colour Chart (BS colour).
Standard aluminium frame colours are Polybond Regal silver metallic gloss epoxy polyester and RAL 9016 white gloss polyester.
Each screen is supplied with 2 x end trims which double as rigid inline linking strips.
End trims/inline links extruded from unplasticised poly vinyl chloride (UPVC) finished in silver J067 or white J664.
Additional linking components are available to allow 2 way, 3 way, 4 way or angular linking.
Framework is finished with 4 x injection moulded Acrylonitrile Butadiene Styrene caps finished in silver RAL 9006 or white RAL 9016.

SUPPLIED WITH:
Each screen is supplied with 2 x stabilising mobile feet each with 2 x castor feet.
Each screen is supplied with 2 x end trims which double as rigid inline linking strips.

CERTIFICATIONS:
Fire Rating EN 13501-1:2007+a1:2009 - B, s1, d0 ASTM E84-16 - Class A.

Unit 1 Era Park
Upper Clatford
Hampshire
SP11 7LW

43 Clerkenwell Rd
Clerkenwell
London
EC1M 5RS

t: +44 (0) 1264 341400
f: +44 (0) 1264 341444
e: sales@erascreens.com
w: www.erascreens.com

Company reg no: 04195401
Vat no: 780 7693 87

