


Product Specification/Data Sheet

PRODUCT DETAILS:	
Product Name:	Dolly
Product Type:	Screen: desk mounted
Product Shape:	Straight, wave or arc
Product Code:	DO/XX.XXD/FS



SPECIFICATION:

Consists of a 28mm thick fabric screen.
Screen height available between 250mm and 600mm.
Screen width available between 400mm and 1800mm.
Internal panel construction is from 2 x 12mm medium density fibreboard (MDF) which are adhered together with 21mm brads with 50mm radius top and bottom corners.
Internal panel upholstered (using water based adhesive) in 1mm thick Camira fabric, generally from the Cara, Lucia, Blazer Lite, Synergy or Blazer ranges.
Desk mounted screens are supplied with 2 x spigot brackets to suit 25mm desk tops (code: FJ25) which are fitted to the bottom of the panel.
Desk mounted screens are manufactured 5mm lower than the ordered height to allow for the standard bracket thickness.
Standard bracket hole positions are 200mm in from each screen edge unless screen width is smaller than 800 wide then these will be 75mm - others available on request.
FJ25 brackets are pressure die cast from aluminium and powder coated.
On average each screen is manufactured from materials with 28% recycled content.
On average each screen is manufactured from materials with 91% recyclable content.
Screens are packaged with a single polythene bag.

SUPPLIED WITH:

Desk mounted screens are supplied with 2 x spigot brackets to suit 25mm desk tops (code: FJ25) which are fitted to the bottom of the panel.

CERTIFICATIONS:

Typical Camira fabrics used are Cara, Lucia, Blazer Lite, Synergy or Blazer which have flammability performance as follows, Cara: EN 1021-1 (cigarette), BS 476 Part 7 Class 1 (Adhered), EN 13501-1 Adhered Class B, s2, d0. Lucia: same as Cara plus EN 1021 - 2 (match), BS 7176 Low Hazard, EN 13501-1 Un-adhered class B, s1,d2. Blazer Lite: BS 476 Part 7 Class 1 (Adhered), BS 476 Part 6 Class 0 (Adhered), EN 13501-1 Adhered Class C, s1, d0. Synergy: EN 1021 - 1 (cigarette), EN 1021 - 2 (match), BS 7176 Low Hazard, NF D 60-013, ÖNORM B 3825 & A 3800-1, (58 kg/m3 CMHR Foam), UNI 9175 Classe 1 IM, EN 13501-1 Adhered Class D, s1, d0, EN 13501-1 Un-adhered Class E, s2, d0. Blazer: same as Synergy plus BS 476 Part 7 Class 1 (Adhered).
Conforms to BSEN 1023 part 1.
Tested by the Furniture Industry Research Association (FIRA) and certified to BSEN 1023 parts 2 & 3 - report reference TREL32922.