Product Specification/Data Sheet

era
bespoke - flexible - service

PRODUCT DETAILS:

Product Name:	Eden
Product Type:	Fabric tile
Product Shape:	Quad, hexagon, fan, rhombus, circle, doughnut, cloud.
Product Code:	ED(W/C)/XX.XX.XX

PRODUCT IMAGE:

SPECIFICATION:

- Consists of either a 40mm or 64mm thick fabric tile.
- Tile width available between 200mm and 1600mm.
- Tile depth available between 200mm and 1600mm.
- Tile construction is from 12mm medium density fibreboard (MDF) adhered (using water based adhesive) to either 25mm or 50mm sound absorbing foam.
- Sound absorbing foam is tested to BSEN ISO 354 and has a noise reduction co-efficient (NRC) of 0.55 for 25mm thick and 0.90 for 50mm thick. Technical report ref no: C/23213/T01.
- Tile is upholstered (using water based adhesive) in 1mm thick Camira fabric, generally from the Cara, Blazer Lite, Synergy or Blazer ranges.
- Wall mounted tiles are supplied with self adhesive PS51/PS52 Ultramate Industrial Strength Velcro.
- Ceiling hung tiles are supplied with 4 x hanging wire kits consisting of 1.5mm diameter steel cables and 2 x satin chrome ceiling and panel brackets.
- On average each tile is manufactured from materials with 31% recycled content.
- On average each tile is manufactured from materials with 71% recyclable content.
- Screens are packaged with a single polythene bag.

SUPPLIED WITH:

- Wall mounted tiles are supplied with self adhesive PS51/PS52 Ultramate Industrial Strength Velcro.
- Ceiling hung tiles are supplied with 4 x hanging wire kits consisting of 1.5mm diameter steel cables and 2 x satin chrome ceiling and panel brackets.

CERTIFICATIONS:

- Typical Camira fabrics used are Cara, Blazer Lite, Synergy or Blazer which have flammability performance as follows, Cara: EN 1021-1 (cigarette), BS 476 Part 7 Class 1 (Adhered), EN 13501-1 Adhered Class B, s2, d0. Blazer Lite: BS 476 Part 7 Class 1 (Adhered), BS 476 Part 6 Class 0 (Adhered), EN 13501-1 Adhered Class C, s1, d0. Synergy: EN 1021 - 1 (cigarette), EN 1021 - 2 (match), BS 7176 Low Hazard, NF D 60-013, ÖNORM B 3825 & A 3800-1, (58 kg/m3 CMHR Foam), UNI 9175 Classe 1 IM, EN 13501-1 Adhered Class D, s1, d0, EN 13501-1 Un-adhered Class E, s2, d0. Blazer: same as Synergy plus BS 476 Part 7 Class 1 (Adhered).
- Conforms to BSEN 1023 part 1.
- Tested by the Furniture Industry Research Association (FIRA) and certified to BSEN 1023 parts 2 & 3 - report reference TRELF32922.

Unit 1 Era Park
Upper Clatford
Hampshire
SP11 7LW

First Floor
10 Great Sutton Street
London
EC1V 0BX

t: +44 (0) 1264 341400
f: +44 (0) 1264 341444
e: sales@erascreens.com
w: www. erascreens.com

Company reg no: 04195401
Vat no: 780 7693 87